

In the specification:

Page 10, third paragraph:

- - The attachment device 420 is comprised of bolt 420a, spacer 420b, hex nut 420c, and washer 420d. Similarly the attachment device 422 is comprised of bolt 422a, spacer 422b, ~~spacer~~ hex nut 422c, and washer 422d. The attachment devices 420 and 422 fix the member 416 to the top plate 412. - -

Page 10, fourth paragraph – pg. 11, first paragraph:

-- The pins 430 include all the pins located in the row at the rear of the pest control device 410 as shown by Figs. 1B and 6B. As shown in Figs. 1B, 2B, and 3B, pins 430 would be located furthest away from the door 101. The pins ~~430~~ 440 include all the pins in a middle row of the pest control device 410 as shown in Fig. 6B. The pins 450 include all the pins located in a row near the front of the pest control device 410 as shown in Figs. 4B and 6B. Each of the pins 430, 440, and 450 is inserted through holes in member 416. For example, pin 430a is inserted through hole 431a in member 416. The location of hole 431a is shown by dashed lines in Fig. 8B. Each of the pins 430, 440, and 450 have a head, which prevents them from falling through the member 416. For example pin 30a has a head 31a and pin 450a has a head ~~51a~~ 451a shown in Fig. 8B. --